

Right-angle coaxial adapter with N-type and SMA connectors, operating frequency range from DC to 18 GHz, VSWR is 1.10 typ., dielectric withstanding voltage is 1000 V.

TYPICAL APPLICATIONS

- Connecting different types of coaxial connectors
- Test and measurement equipment in RF or microwave engineering
- Antenna systems and RF installations
- Cable TV and satellite communication
- Telecommunications infrastructure
- Military and aerospace communication systems

FEATURES

- Small size
- Low VSWR

MECHANICAL SPECIFICATIONS


Inner conductor material	Gold-plated beryllium copper
Dielectric material	PEI
Housing	Passivated stainless steel
Coupling nut material	Passivated stainless steel
Operating temperature, °C	-20 – +60
Dimensions, mm	Check the outline drawings

ELECTRICAL SPECIFICATIONS

Operating frequency, GHz	18
Dielectric withstanding voltage, V	1000
VSWR	1.10 typ. / 1.20 max.
Insulation resistance, MOhm	5000
Insertion loss, dB	0.25

NOMINAL IMPEDANCE: 50 Ohm

CONNECTOR TYPES: **N** male;
SMA female


Notes:

1. All outline dimensions are in mm, with a dimensional tolerance of $\pm 5\%$.
2. Insertion loss is calculated as $0.05\sqrt{f}$, where f is the frequency in GHz.
3. Sizes marked with *are only for reference.