



Series of coaxial adapters with 1.35 mm and 1.0 mm connectors, operating frequency range from DC to 90 GHz, VSWR is 1.40, dielectric withstanding voltage is 500 V.

TYPICAL APPLICATIONS

- Connecting different types of coaxial connectors
- Test and measurement equipment in RF or microwave engineering
- Antenna systems and RF installations
- Cable TV and satellite communication
- Telecommunications infrastructure
- Military and aerospace communication systems

FEATURES

- Small size
- Low VSWR



MECHANICAL SPECIFICATIONS

Inner conductor material	Gold-plated beryllium copper
Dielectric material	PEI
Housing	Passivated stainless steel
Coupling nut material	Passivated stainless steel
Operating temperature, °C	-20 – +60
Dimensions, mm	Check the outline drawings

ELECTRICAL SPECIFICATIONS

Operating frequency, GHz	90
Dielectric withstanding voltage, V	500
VSWR	≤1.40
Insulation resistance, MOhm	5000
Insertion loss, dB	≤0.60

NOMINAL IMPEDANCE: 50 Ohm

CONNECTOR TYPES: 1.35 mm female;
1.0 mm male/female

Ordering information:

LBWT-AC-90-1.35F-1.0X — specify connector genders
(Female/Male; Female/Female)

Notes:

1. All outline dimensions are in mm, with a dimensional tolerance of ±5%.